

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 April 2008 (10.04.2008)

PCT

(10) International Publication Number
WO 2008/040812 A1

(51) International Patent Classification:
A61B 10/00 (2006.01) *B01L 3/00* (2006.01)
A61B 10/02 (2006.01)

(21) International Application Number:
PCT/EP2007/060615

(22) International Filing Date: 5 October 2007 (05.10.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/850,004 6 October 2006 (06.10.2006) US

(71) Applicants (for all designated States except US):
Sonion Roskilde A/S [DK/DK]; Byleddet 12-14,
DK-4000 Roskilde (DK). Danborg Innovation [DK/DK];
Solvangsvej 28, DK-2600 Glostrup (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VIDEBAEK,
Karsten [DK/DK]; Toftager 24, St. Valby, DK-4000
Roskilde (DK). STAAL, Lasse G. [DK/DK]; Ericavej 5,
DK-4040 Jyllinge (DK). GUNDBERG, Tomas [DK/DK];
Vinkelvej 4, DK-4130 Viby Sjaelland (DK). DANBORG,
Lasse [DK/DK]; Solvangsvej 28, DK-2600 Glostrup
(DK).

(74) Agent: INSPICOS A/S; P.O. Box 45, Bøge Allé 5,
DK-2970 Hørsholm (DK).


(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG,
ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK,
LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW,
MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL,
PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL,
PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(54) Title: TISSUE HANDLING SYSTEM WITH REDUCED OPERATOR EXPOSURE



(57) Abstract: A tissue handling system includes a biopsy device having an invasive unit with tissue-receiving and tissue-severing components being capable of harvesting and bringing at least one tissue sample to a point outside the body of a patient. The tissue handling system further includes a tissue collecting device adapted to be brought in detachable operative engagement with the tissue-receiving components of the biopsy device to remove the at least one tissue sample. Additionally, the tissue handling device comprises a tissue storage container configured to receive the at least one tissue sample, the entire tissue collecting device, or the part of the collecting device that contains the at least one tissue sample. The tissue storage container further being configured to receive a volume of preserving agent. The tissue handling system also comprises a vessel including the preserving agent adapted to be gas-tightly mated or coupled to the tissue storage container.

WO 2008/040812 A1

TISSUE HANDLING SYSTEM WITH REDUCED OPERATOR EXPOSURE

Field of the invention

This invention relates to systems for the acquisition and handling of tissue samples and, more particularly, to a system that comprises all necessary means
5 for harvesting, storing and transporting tissue samples without requiring physical handling of the tissue sample by the operator, in an uninterrupted chain that has its point of origin within the body of the patient and has as its point of conclusion the commencement of analysis of the at least one sample by a pathologist or similarly medical skilled professional. More specifically, the
10 invention relates to a system for the acquisition and handling of tissue samples that comprises all necessary means for harvesting, storing and transporting the at least one tissue sample without requiring physical handling of the sample by the operator, in an uninterrupted tissue handling chain that has its point of origin within the body of the patient and has as its point of conclusion the
15 commencement of analysis of the at least one tissue sample by a pathologist or similarly skilled professional, while at the same time protecting the operator and other persons involved in the handling of tissue samples from exposure to potential bio-hazards and bio-contaminants as well as formalin or similar preserving agents that may act as carcinogens.

20 Background of the invention

In modern medicine it is often desirable and frequently necessary to harvest tissue samples from a target tissue region or tissue site inside a human or animal body for the purpose of diagnosing a suspected malignancy. Currently available biopsy devices offer several ways of accessing suspect tissue and of
25 harvesting tissue samples that may be used for diagnostic purposes, and some also comprise temporary storage solutions that may be used to hold tissue samples during a biopsy procedure. Such a biopsy device is disclosed in US patent 5,526,822. The disclosed biopsy device is capable of harvesting multiple tissue samples in a single device insertion and features a cassette with multiple
30 tissue chambers, permitting the temporary storage of multiple tissue samples.

However, none of the currently available biopsy devices and systems address all the functions and provide all the interfaces between functions that are involved in harvesting a tissue sample and getting the tissue sample to the pathologist in uncontaminated or undisturbed condition. Another important aspect of the present invention is to provide biopsy devices and systems that minimize operator exposure to bio-hazards, bio-contaminants as well as formalin and other known and probable human carcinogens. The current lack of commercially available biopsy devices and systems with one or both of these capabilities is problematic for several reasons.

- 10 New and improved diagnostic techniques – such as cytogenetic, immunological and biochemical analyses require that the tissue samples be handled with extreme care. Since tissue architecture is an important parameter in the histologic analysis of samples it is important that handling of acquired tissue samples is minimized.
- 15 Human tissues are potentially infectious, and an operator increases his exposure to such infection by physically handling tissue samples. Given this, limiting operator exposure to tissue samples is a sensible precaution. Currently available systems, such as is disclosed in US 5,526,822, provide means for temporarily storing one or more tissue samples during a biopsy procedure, but
- 20 no means are provided for transferring such tissue samples to more permanent storage containers where preservation and fixation of the tissue samples is possible. In use, these systems therefore require that the operator or an assistant manually transfer samples from the temporary storage means included in the biopsy device to more permanent storage means if said samples are to be
- 25 fixated prior to being sent to a pathologist or similarly skilled individual for analysis.

Another problem that has received little attention in the design of presently available biopsy systems is the use of formalin or similar preserving agents to fixate tissue samples subsequent to their extraction from the patient. Formalin

30 is classified by the WHO and IARC as a known carcinogen and at least some countries have imposed limits on the permissible exposure. These limits include

upper limits on the amount of airborne formalin and such upper limits have forced some hospitals to implement ventilation and suction systems to protect doctors and assistants from excessive exposure to formalin. Such implementation programs – when possible - are costly and potentially disruptive to established biopsy procedure routines.

Therefore, a biopsy device and system according to the present invention that comprise all necessary components and functionalities for safely and efficiently harvesting one or more tissue samples in a single device insertion are highly advantageous. Furthermore, such biopsy device and system may advantageously comprise means for temporarily storing harvested tissue samples in individual compartments during the biopsy procedure while permitting the operator/doctor to inspect each tissue sample for adequacy, as well as means for more permanently storing and fixating the samples once the harvesting is over. Ideally, transfer of the tissue samples between the temporary storage means included in the biopsy device and the permanent storage means should be possible without requiring that the operator removes the samples from their individual compartments thereby minimizing the exposure of the operator to bio-hazards and bio-contamination. In addition, such a comprehensive a biopsy device and system would also provide means for aggregating formalin or a similar preserving and fixating agent while maintaining at all times a closed environment, to eliminate operator exposure to such substances.

Summary of the invention

In a first aspect, the present invention provides a tissue handling system comprising:

- a biopsy device having an invasive unit with tissue-receiving and tissue-severing components being capable of harvesting and bringing at least one tissue sample to a point outside the body of a patient;
- a tissue collecting device adapted to be brought in detachable operative engagement with the tissue-receiving components of the biopsy device to remove the at least one tissue sample;

- a tissue storage container configured to receive the at least one tissue sample, the entire tissue collecting device, or the part of the collecting device that contains the at least one tissue sample, the tissue storage container further being configured to receive a volume of preserving agent; and
- 5 - a vessel adapted to contain the preserving agent adapted to be gas-tightly mated or coupled to the tissue storage container.

Preferably, structure is provided for transferring (i.e. conveying or moving) the preserving agent in the vessel to the tissue storage container. As the tissue collecting device may be detached from the remaining components of the biopsy
10 device and placed in the tissue storage container, which in turn may be partially or fully filled with the preserving agent deriving from the vessel, a convenient way of transferring tissue samples from the biopsy device to a storage container is provided.

A compartment in the vessel for storing the preserving agent may be closed by a
15 liquid and gas tight closure, which is releasable when the vessel is mated or coupled to the tissue storage container. In one embodiment, preserving agent may be released following a predefined user action, such as removal of a separate seal or closure or activation of a syringe plunger. In other
20 embodiments, release of the closure to convey preserving agent from the vessel may occur automatically as a consequence of attachment of the vessel to the tissue storage container. For example, the tissue storage container and the vessel may comprise a connecting structure for gas-tightly mating or coupling
25 the vessel to the tissue storage container. Hence, the connecting structure may be arranged to cause the closure to be released as a consequence of mating or coupling the vessel to the tissue storage container.

The vessel may be comprised in a lid for closing the tissue storage container. In one embodiment, the lid is attachable to the tissue storage container in such a way that a first attachment action establishes a gas tight coupling of the vessel to the tissue storage container, and a second attachment action causes release
30 of the closure. The tissue storage container and the lid are preferably arranged such that the second attachment action cannot occur prior to the first

attachment action. The first attachment action may e.g. include an axial displacement of the parts relative to each other, whereas the second attachment action may e.g. include a mutual twisting of the parts. The parts may be shaped and configured such that the twisting, which causes release of the closure cannot occur, before the parts are arranged in the correct axial inter-relationship. Preferably, the closure may be resealed following a third pre-defined user action, such as e.g. a further mutual twisting of the parts, to prevent the preserving agent from flowing back from the tissue storage container into the vessel.

- 10 In other embodiments, the vessel may include a syringe, and the tissue storage container may comprise a connecting mechanism for gas-tightly mating or coupling the syringe to the tissue storage container, such as a luer lock or a septum.

- 15 The collecting device of the biopsy device may comprise a collecting unit which comprises a plurality of individual tissue chambers, and wherein the collecting device is capable of sequentially removing, from the tissue-receiving components of the biopsy device, a plurality of individual tissue samples as they are excised from the body of the patient and of temporarily storing the tissue samples in individual tissue chambers. Alternatively, the tissue samples may be temporarily stored in one single bulk in said chamber.

Suitable devices for harvesting and temporarily storing tissue samples are disclosed in International Patent Application No. PCT/DK2007/000166, which is hereby incorporated by reference.

- 25 The volume of preserving agent in the vessel is preferably sufficient to cover the at least one tissue sample when stored in the tissue storage container.

In a second aspect, the present invention provides a method of handling at least one harvested biopsy tissue sample, the method comprising:

- providing the at least one tissue sample in tissue-receiving components of a biopsy device outside the body of a patient;

- detachably engaging a tissue collecting device to said tissue-receiving components;
- arranging the at least one tissue sample, the entire tissue collecting device, or the part of the collecting device that contains the at least one tissue sample in a tissue storage container;
- gas-tightly mating or coupling a vessel containing a volume of a preserving agent to the tissue storage container;
- transferring the volume of preserving agent from the vessel to the tissue storage container, when the vessel is gas-tightly mated or coupled to the tissue storage container.

The features of the system of the first aspect of the invention and their intended method of use may be incorporated in embodiments of the method of the second aspect of the invention.

- It will hence be understood that the vessel may include a compartment for storing the preserving agent, wherein the compartment is closed by a liquid and gas tight closure, and wherein the closure is released from a closed condition to an open condition, when the vessel is mated or coupled to the tissue storage container. The closure may be caused to be released as a consequence of mating or coupling the vessel to the tissue storage container. The vessel may be comprised in a lid for closing the tissue storage container, and the lid may be attached to the tissue storage container in such a way that a first attachment action establishes a gas tight coupling of the vessel to the tissue storage container, and a second subsequent attachment action causes release of said closure. A third subsequent action may cause closing of the closure to prevent preserving agent from flowing back from the tissue storage container to the vessel.

- The method may further comprise, subsequently to the step of transferring, the further step of conveying the tissue storage container with the at least one tissue sample container therein from a first handling site to a second handling site, when the tissue sample container is closed by said lid. The first handling site may e.g. be provided close to the patient, e.g. on a working desk of the

surgeon performing the biopsy procedure, and the second handling site may e.g. be provided at a remote location, such as the analysis site of the pathologist.

In a third aspect, the invention provides a system for storing at least one harvested biopsy tissue sample, the system comprising:

- 5 - a tissue storage container capable of receiving and storing the at least one tissue sample;
- a vessel containing a volume of a preserving agent;
- a connecting structure for gas-tightly mating or coupling the vessel to the tissue storage container;
- 10 - a fluid transferring mechanism for causing a transfer of the volume of preserving agent from the vessel to the tissue storage container, when the vessel is gas-tightly mated or coupled to the tissue storage container.

The features of the system of the first aspect of the invention and the method of the second aspect of the invention also apply to the system of the third aspect of the invention. It will hence be appreciated that the vessel may have a

15 compartment for storing the preserving agent, wherein the compartment is closed by a liquid and gas tight closure, the closure being releasable when the vessel is mated or coupled to the tissue storage container. The tissue storage container and the vessel may comprise a connecting structure for gas-tightly

20 mating or coupling the vessel to the tissue storage container, and the connecting structure may be arranged to cause the closure to be released as a consequence of mating or coupling the vessel to the tissue storage container. The vessel may be comprised in a lid for closing the tissue storage container. The lid may be

25 attachable to the tissue storage container in such a way that a first attachment action establishes a gas tight coupling of the vessel to the tissue storage container, and a second attachment action causes release of said closure, the tissue storage container and the lid being arranged such that the second attachment action cannot occur prior to the first attachment action. A third

30 subsequent action may cause closing of the closure to prevent preserving agent from flowing back from the tissue storage container to the vessel.

The vessel may include a syringe, and the tissue storage container may comprise a connecting mechanism for gas-tightly mating or coupling the syringe to the tissue storage container.

5 The vessel may be adapted to contain a volume of preserving agent, which is sufficient to cover the at least one tissue sample when stored in the tissue storage container.

10 It will be appreciated that the system of the third aspect of the invention may be used to cause the transfer of any matter into any kind of container. Hence, the system of the third aspect of the invention may be for storing any kind of material with any kind of liquid or gas, or for mixing two components, such as two kinds of liquid, two kinds of powders, or for mixing liquid into solid matter or powder.

15 In a fourth aspect, the present invention provides a vessel for a system according to the third aspect of the invention, said system comprising a tissue storage container capable of receiving and storing at least one tissue sample, the vessel comprising:

- a cavity containing a volume of a tissue preserving agent;
- connecting elements for gas-tightly mating or coupling the vessel to the tissue storage container;
- 20 - fluid transferring element for causing a transfer of the volume of preserving agent from the vessel to the tissue storage container, when the vessel is gas-tightly mated or coupled to the tissue storage container.

25 The vessel may include the features described above with reference to the systems of the first and third aspects of the invention as well as the features described above with reference to the method of the second aspect of the invention.

The vessel may hence comprise a compartment for storing the preserving agent, wherein the compartment is closed by a liquid and gas tight closure, said closure being releasable when the vessel is mated or coupled to the tissue storage

container. The vessel may be comprised in a lid for closing the tissue storage container.

From the above description, it will be appreciated that embodiments of the various aspects of the present invention provide a comprehensive tissue
5 sampling system that solves the above-mentioned and other problems by comprising the following:

A. A biopsy device comprising an invasive unit with tissue-receiving and tissue-severing components that is capable of harvesting and bringing to a point outside the body of a patient one or more tissue samples.

10 B. A tissue collecting device that may be brought in detachable operative engagement with the tissue-receiving components of the biopsy device to remove the at least one tissue sample. Said tissue collecting device may optionally comprise one or more tissue chambers for temporary storage of tissue samples during a biopsy procedure. If more than one chamber is available, said
15 chambers may sequentially move or be moved into operative engagement with the tissue-receiving components to collect and individually store tissue samples. By suitable configuration of the tissue collecting device, the sequence and spatial orientation of the acquired tissue samples may be maintained at all times and tissue samples may be supported and protected while they are temporarily held
20 in the tissue collecting device.

C. A tissue storage container that is configured to receive either the one or more tissue samples, the entire tissue collecting device or the part of the collecting device that contains the one or more tissue samples. The tissue storage container is furthermore configured to receive a volume of preserving
25 agent while comprising a sealed receptacle that provides a substantially sealed enclosure for the gaseous and liquid phases of the preserving agent.

D. A vessel containing the preserving agent that may be gas-tightly mated or coupled to the tissue storage container and inject the preserving agent into the tissue storage container. Said vessel should preferably contain an

amount of preserving agent that is sufficient to cover the at least one tissue sample that is housed in the tissue storage container.

In a particular embodiment, the invention provides a comprehensive tissue sampling system comprising:

- 5 A. A multiple biopsy device comprising an invasive unit with tissue-receiving and tissue-severing components that is capable of harvesting and bringing to a point outside the body of a patient a plurality of individual tissue samples in a single device insertion
- 10 B. An automatic tissue collecting device that is in detachable operative engagement with the multiple biopsy device. Said tissue collecting device comprises a housing and a collecting unit that comprises a plurality of individual tissue chambers and is held in the housing by means of a collecting unit lid that is releasably attached to the housing. Said tissue collecting device is capable of sequentially removing from the tissue-receiving components of the biopsy device
15 a plurality of individual tissue samples as they are excised from the body of the patient and of temporarily storing these tissue samples in individual tissue chambers while maintaining at all times the spatial orientation of said samples relative to their positions at the point of sampling. Following completion of a biopsy procedure, the tissue collecting device may be detached from the biopsy
20 device and the collecting unit along with the lid may be removed from the housing and transferred to a tissue storage container while still containing the samples. Thus, physical manipulation of individual samples is avoided.
- 25 C. A tissue storage container that is configured receive the collecting unit of the tissue collecting device and to house said collecting unit along with the samples that are stored in the tissue chambers of the collecting unit. The tissue storage container comprises a receptacle that may be air-tightly mated to a tissue storage container lid and is configured to receive and support the collecting unit. The capacity of the receptacle is dimensioned to ensure that sufficient preserving agent is available to provide proper fixation of the individual samples.

The tissue storage container lid may be configured to mate with the lid of the collecting unit, permitting the operator to remove the collecting unit from the housing by holding the tissue storage container lid and the housing, thus avoiding physical manipulation of individual tissue samples. Furthermore, the tissue storage container lid may be configured to act as a reservoir for a preserving agent and comprises a fully enclosed cavity as well as means for gas-tight mating or coupling to a vessel containing a preserving agent. Suitable configuration of said vessel will provide gas-tight ingress and subsequent controlled egress of said preserving agent into the receptacle. Such means of controlled egress may be configured to provide a user-activated gas – and fluid-tight seal between the storage container lid and the receptacle. Such a seal may be activated subsequent to the egress of the preserving agent from the tissue storage container lid, efficiently limiting the volume of preserving agent needed to adequately cover the samples by keeping the preserving agent contained in the receptacle. Thus, if the amount of preserving agent applied prior to activation matches the capacity of the receptacle, and if the tissue storage container is suitably oriented during egress, it is ensured that the samples will be adequately covered while they are kept in the tissue storage container. If the means of ingress are furthermore configured to act as a gas-tight seal following removal of the vessel, substantially all the air and vapors of preserving agent that is contained in the storage container lid subsequent to the egress of said agent may be encapsulated in said lid. Thus, if ingress and subsequent egress of the agent is done subsequent to attachment of the tissue storage container lid to the receptacle, the lid may act as an air lock, permitting the ingress of the preserving agent into the tissue storage container while at the same time preventing vapors of said agent from escaping from said container to the surrounding environment. By suitable configuration of the user-activated seal, the air and preserving agent that is thus contained may remain encapsulated in the tissue storage container lid even after the lid is removed from the receptacle.

D. A vessel containing formalin or similar preserving agent that is configured as a syringe and may be detachably and air-tightly mated to the ingress means of

the lid of the tissue storage container. Said syringe may comprise means for injecting the formalin at a pressure exceeding the atmospheric pressure. This capability is desired since injection of the preserving agent is done into a gas-tightly sealed container that is filled with air at atmospheric pressure prior to injection. As the preserving agent is injected into the storage container, the air in said container is compressed in correspondence with the volume of preserving agent injected. If the tissue storage container is placed with the receptacle in a lower position relative to the tissue storage container lid during injection, and the preserving agent is in a fluid phase, the laws of gravity will cause the preserving agent to move towards the bottom of the receptacle while the air that fills the container will be urged toward the top of the lid. If the capacity of the tissue storage container lid is sufficient or the amount of preserving agent is minimal compared with the amount of air, the operator should have to expend an absolute minimum of force while injecting the preserving agent. Alternatively, suitably configured tools may be provided to assist the operator.

An important advantage of the comprehensive biopsy system according to preferred embodiments of the invention is that it provides extensive protection of the operator from liquid or gaseous components of potentially toxic and/or carcinogenic preserving agents by maintaining for the duration of the procedure all such agents in gas-tight enclosures. As an additional benefit associated with preferred embodiments of such a system, the operator is provided with means of transferring one or more tissue samples from a biopsy device to a preserving agent without having to physically manipulate individual tissue samples. Thus, operator exposure to bio-hazards and bio-contaminants is to a large extent avoided.

According to one embodiment, the ingress means for the preserving agent comprise a female luer lock that is operatively connected to a one-way valve, where the one-way valve is configured to permit the passage of formalin into the container lid while at the same time preventing the escape of air and vapors of preserving agent once the syringe has been removed from airtight connection with the ingress means of the storage container lid.

The egress means comprise a rubber membrane that is an integral part of the container lid. Said rubber membrane features a number of holes. A plastic disc is a removable part of the receptacle and has an equal number of holes that may be brought into alignment with the holes in the rubber membrane. When the storage container lid is placed on the receptacle, the plastic disc is brought to abut and contact the rubber membrane. Alignment of the holes in the rubber membrane and the plastic disc may be done by twisting or rotating the storage container lid to a first locking position. In said first locking position, the storage container lid is air-tightly mated with the receptacle, and formalin may pass from the reservoir that is comprised in the storage container lid to the receptacle to fully cover the tissue samples that are placed in said receptacle.

When the storage container lid is subsequently twisted to a second locking position, airtight mating is maintained while the holes in the rubber membrane are twisted out of alignment with the holes in the plastic disc. Furthermore, the plastic disc is fixedly abutted to the storage container lid and is locked in place resting against – and providing support to – the rubber membrane. In the second locked position, the rubber membrane and the plastic disc thus co-act to provide an airtight and fluid-tight barrier between the formalin that is held in the receptacle and the air that is held in the storage container lid.

Such a separation is advantageous, provided that the receptacle is substantially filled with the preserving agent when the seal is activated, as it ensures that the tissue samples are covered by the preserving agent, e.g. formalin, independent of the orientation of the tissue storage container during transport or other handling since the receptacle will be completely filled.

Yet another advantage with the present system is that the collecting unit, the housing and the tissue storage container may be given unique and identical numbers, bar-codes or similar means of identification – prominently displayed to improve traceability and minimize the risk that tissue samples from one patient are mistakenly mixed up with tissue samples from another patient.

A further advantage of a tissue storage container of such a configuration is that the preserving agent and all vapors of said agent are maintained in airtight enclosures. In some of the envisioned embodiments, such vapors may be kept fully enclosed in the storage container lid until disposal – even after the lid is separated from the receptacle. Further, if opening of the tissue storage container is only done in a pathologist lab or similar facility characterized by the availability of adequate suction/ventilation and other protective equipment, operator exposure should be strongly reduced or entirely eliminated.

In one particular embodiment, the receptacle comprises a net that may enclose the collecting unit and is configured to hold the samples in place in their individual chambers to ensure that they maintain at all times their spatial orientation while at the same time permitting the preserving agent to diffuse into the tissue samples for proper fixation.

In a variant of this embodiment, the net comprises a plastic frame with a threaded section that is configured to mate with locking pins in the lid of the collecting unit.

In one particular variant, the net is removably positioned in the center of the opening of the receptacle and mating takes place when the storage container lid is twisted to its first position. When the storage container lid is subsequently twisted to its second, locked position, the net is twisted along with the lid, maintaining the connection. When the storage container lid is subsequently removed from the receptacle, the net stays attached to the lid of the collecting unit, ensuring that the tissue samples maintain their mutual spatial orientation until the net is removed by a pathologist or similarly trained individual. This feature is particularly advantageous in the harvesting of tissue samples in the prostate, where samples are harvested according to specific systems or methodologies. Since the absence or presence of prostate cancer in specific samples may ultimately determine the choice of treatment, the preserving the order and spatial orientation of the individual samples is crucial.

In an alternative embodiment, the lid of the tissue storage container is pre-filled with the preserving agent and the plastic disc is an integral part of the storage container lid. This permits the elimination of the separate vessel and provides a more user-friendly alternative to the system described above.

- 5 Additional aspects of the invention will be apparent to those of ordinary skill in the art in view of the detailed description of various embodiments, which is made with reference to the drawings, a brief description of which is provided below.

Brief description of the drawings

- 10 Fig. 1 is a semi-frontal view of a disposable unit according to an aspect of the present invention.

Fig. 2 is a semi-frontal view of a hand-piece according to an aspect of the present invention

Fig. 3 is a more detailed view of the collecting unit and the collecting unit lid.

- 15 For clarity, the housing has been removed.

Fig. 4 is an exploded view of the collecting unit with the housing removed as it is being mated to the lid of a tissue storage container.

Fig. 5 is an upward-looking view of the collecting unit after being mated to the lid of a tissue storage container.

- 20 Fig. 6 shows a simple receptacle of a tissue storage container, the receptacle being primarily configured to receive larger tissue samples such as those produced by an open biopsy.

- Fig. 7 shows a receptacle of a tissue storage container, the receptacle being more specifically suited to applications with multiple biopsy devices with a net
25 that is configured to enclose the collecting unit of a tissue collecting device.

Fig. 8 shows a receptacle for a tissue storage container similar to the receptacles disclosed in figures 6 and 7, with a plastic lid that is a part of a user-activated seal.

5 Fig. 9 is an upward-looking view of the collecting unit as it is inserted into the net that is comprised in one particular embodiment of the receptacle of the tissue storage container. For clarity, the tissue storage container with its receptacle is omitted from this figure.

Fig. 10 is an upward-looking view of the collecting unit after being inserted into and firmly attached to the net described in figure 6.

10 Fig. 11 shows a tissue storage container lid comprising a luer lock with an operatively connected one-way valve that is configured to receive a syringe. In one embodiment of this invention, the syringe is used to inject formalin into the tissue storage lid, wherefrom it passes into the receptacle of the tissue storage container to cover the tissue samples that are housed in the tissue collecting
15 unit.

Fig. 12 shows a tissue storage container lid similar to that of figure 11, but with a septum instead of a luer lock.

Figs. 13-20 show the operating sequence of the transfer of tissue samples from the temporary storage of a tissue collecting device to the more permanent
20 storage and fixation according to a specific embodiment of the present invention.

Figs. 21-24 illustrate an embodiment of a tissue storage container, the lid of which itself constitutes a vessel for containing a preserving agent.

Detailed description of the drawings

25 Figures 1 and 2 show a multiple biopsy device that is particularly well suited to form part of a comprehensive tissue sampling system in accordance with the

invention. The biopsy device comprises a disposable unit with invasive components 1, comprising a cutting cannula 102 and a tissue-receiving container 104 that is movably received in an inner lumen of the cutting cannula 102 in response to the motions of a toothed rack that is attached to the proximal
5 end of said tissue-receiving container, the toothed rack being in turn driven by a motor (not shown).

The biopsy device may include embodiments of the device claimed and described in International Patent Application No. PCT/DK2007/000166, which is hereby incorporated by reference.

10 Operatively coupled to this disposable unit is a hand-piece, shown in Fig. 2. The hand piece includes a power source, a vacuum unit, a motorized driver unit and a user interface 2 comprising twin buttons and a means for visually inspecting a tissue sample at a suitable point in time. By comprising these and other
15 components, said device provides a fully automated tissue harvesting mechanism that is capable of sequentially harvesting multiple tissue samples and bringing these to a point outside the body of a patient.

Furthermore, the device comprises an automatic tissue collecting device 3 (Fig. 1), at least part of which is in operative engagement with the disposable unit. Said tissue collecting device may comprise a collecting unit 4 (Fig. 3) that is
20 stepwise rotatable about a central axis and is detachably received in a housing 5 (Fig. 1).

As shown in Fig. 3, a lid 6 is attached to the collecting unit and is configured to releasably interface with the housing to hold the collecting unit in place in the housing for the duration of a biopsy procedure. The lid is furthermore
25 configured to mate with a tissue storage container lid 7 (Fig. 5), according to a tissue transfer procedure from temporary storage to permanent storage, as shown in Figs. 4 and 5.

Figs. 6-8 show different receptacles of tissue storage containers for biopsy samples.

Fig. 6 shows a receptacle of a tissue storage container, the receptacle being primarily suited to larger tissue samples that may be placed directly in a trough 8, such as those harvested in an open biopsy. A plastic disc that may form part of a user-activated seal has been omitted from the drawing for the sake of simplicity. However, it should be understood that such a disc may be needed to provide a gas-tight enclosure at all times. It is envisaged that such a receptacle, coupled to a tissue storage container lid, will provide general surgeons with, for example, an advantageous means of protecting themselves against excessive exposure to preserving agents, such as formalin, while handling the tissue samples.

Fig. 7 shows a receptacle of a tissue storage container, the receptacle being configured to interface with multiple biopsy devices such as the one shown in Figs. 1 and 2. The receptacle comprises a net 9 that is removably suspended centrally over the through and is configured to receive and enclose a collecting unit of the biopsy device. Said net may comprise a supporting frame of plastic or similar material with structure for releasably mating with the lid of the collecting unit. Such structure may for instance comprise two or more locking grooves that are formed in the frame and are configured to receive two or more locking pins that are formed in the collecting unit lid. Such a net is thought to be of particular relevance in the sampling of lesions in the prostate, where the sequence and orientation of tissue samples relative to their origin in the sampled tissue is crucial. For such applications, it is important to ensure that the tissue samples – or fragments of these – do not drift away from the tissue chambers where they were originally placed. The net should therefore be comprised of a very fine mesh. Figs. 9 and 10 show the collecting unit 4 and the net 9 before and after mating. For the sake of simplicity, the tissue storage container with its receptacle is omitted.

In addition to the above, the net 9 may also be used to house a plurality of individual tissue samples, such as those harvested with a conventional core needle or a multiple biopsy device without a tissue collecting device. Such samples may either be placed directly in the net, or they may be kept separate. This may, for instance, be accomplished by providing a net that is or may be

divided into smaller compartments. This may be accomplished by inserting suitably configured partitions that are supported by the plastic frame, for example.

Fig. 8 shows a receptacle of a tissue storage container, the receptacle being similar to the receptacle of Figs. 6 and 7, but according to this variant, a plastic disc 10 is removably placed over the trough 8 of the receptacle. Said plastic disc 10 comprises a plurality of holes 16 that may be aligned with a similar plurality of holes 17 in a rubber membrane 11 to provide a fluid path (Fig. 5). The membrane is an integral part of the tissue storage container lid. These two components may be combined to comprise a gas and fluid tight seal between the tissue storage container lid and the trough 8 of the receptacle. In a particular embodiment, the combination is accomplished by mating the plastic disc 10 with the tissue storage container lid by means of at least two essentially rectangular locking bars 12 (Fig. 9). The bars 12 are formed in the outer periphery of the plastic disc 10 and are configured to slide in at least two recesses 13 in the rim of the receptacle (Fig. 6). The length of these recesses determines the free rotating motion that the plastic disc may perform relative to the receptacle. Said locking bars may be brought in operative engagement with at least two locking recesses (not shown). Said locking recesses are formed in the rim of the tissue storage container lid as said lid is twisted towards its second locked position. When this is done, the plastic disc 10 is held stationary relative to the twisting motion of the tissue storage lid, and the holes 17 in the rubber membrane 11 are twisted out of alignment with the holes 16 in the plastic disc 10. In this position, the rubber membrane 11 and the plastic disc 10 comprise a user-activated seal that is gas-and fluid-tight and may provide a barrier between the tissue storage container lid and the through of the receptacle, independent of the shape or size of said receptacle.

Figs. 11 and 12 show specific ingress means in accordance with specific embodiments of the present invention.

Fig. 11 shows a tissue storage lid that comprises a female luer lock 14 in operative connection with a one-way valve (not shown). Said luer lock is

configured to receive a syringe containing a preserving agent (e.g., formalin) and to provide a gas-tight seal for the duration of injection of the preserving agent, as well as following removal of the syringe.

Fig. 12 shows an alternative embodiment that comprises a rubber septum 15 that may be pierced, for instance, by a hypodermic needle that is coupled to a syringe.

In the following, a particular embodiment of a comprehensive tissue sampling system is used for explanatory purposes, but it is understood that the principles and methods disclosed in this invention are not restricted to usage with this particular system.

When a biopsy is prescribed, the operator may prepare a biopsy device in accordance with the instructions for use for that particular device. The exemplary device that is a part of the comprehensive tissue sampling system is prepared by removing a protective foil from the transport container of a sterile disposable unit and subsequently removing the disposable unit from a transport container therefor.

While maintaining sterility, the operator may then insert and couple the sterile disposable unit to a hand-piece. Coupling energizes the device. The operator may then proceed to carry out a desired number of biopsies in accordance with the instructions for use and the principles of procedure that pertain to that particular type of biopsies, as described e.g. in International Patent Application No. PCT/DK2007/000166, which is hereby incorporated by reference.

During a biopsy procedure carried out with the exemplary device, tissue samples are sequentially harvested and placed in a tissue-receiving container. Said tissue-receiving container is then transported to a point outside the body of the patient that corresponds with an automatic tissue-collecting device.

Said tissue-collecting device is a part of the disposable unit. It comprises means for ejecting a plurality of sequentially arriving tissue sample from the tissue-

receiving container and of temporarily storing said plurality of tissue samples in individual tissue chambers. In one particular embodiment, the ejection means comprise a comb-like ejector frame with a plurality of ejector pins. Said ejector pins are temporarily insertable through a plurality of holes in the tissue-receiving container, which is capable of reciprocating motion relative to the tissue-receiving container. The means for temporarily storing a plurality of tissue samples may comprise a cylindrical, drum-like collecting unit with a number of semi-open tissue chambers distributed evenly along – and sunk into – its circumference. A plurality of lands and grooves configured to interface with the ejector pins of the ejector frame are also distributed along the circumference and perpendicular to an axis of rotation. Said collecting unit is movably housed in a housing that is releasably attached to the remainder of the disposable unit, and is stepwise rotatable about a central axle to sequentially expose each of a plurality of tissue chambers to receive a tissue sample. A collecting unit lid is configured to releasably hold the collecting unit in place in the housing by providing at least one locking pin releasably received in at least one locking recess in the inner periphery of the housing.

When a tissue sample has been harvested and transported to a point corresponding with the automatic tissue-collecting device, said device is energized by means comprised in the hand-piece. The ejector frame is moved from a first lowered position towards a second raised position, through which movement the plurality of ejector pins are brought in contact with the tissue sample that recedes in the tissue-receiving container. Said contact urges the tissue sample out of the tissue-receiving container and into the exposed opening of one of a plurality of semi-open tissue chambers. Subsequent to this, the collecting unit starts rotating, whereby the lands and grooves of the collecting unit mesh with the fully raised ejector pins. By suitably configuring the points of interception of the grooves and lands with the tissue chambers, fork-like structures may be obtained that may gently support and lift the tissue sample off the ejector pins as these begin their motion towards their first lowered position.

The fork-like structure is shown in Fig. 3. Thus, the tissue-receiving chamber may be emptied without requiring the intervention of an operator, and the tissue-receiving container may be repositioned in the anatomy of the patient to receive another tissue sample.

- 5 By repeating the above procedure a desired number of times, a desired number of biopsy samples may be harvested in a single device insertion.

Such and other embodiments of tissue harvesting and collecting systems are described further in International Patent Application No. PCT/DK2007/000166, which is hereby incorporated by reference.

- 10 Subsequent to the harvesting of the desired number of biopsy samples, the device may be removed from the anatomy of the patient. By decoupling the disposable unit from the hand-piece, access to the tissue-collecting device may be obtained. Subsequently, the housing – along with the collecting unit and the collecting unit lid – may be detached from the disposable unit, as shown in Fig.
15 13.

A significant advantage of the invention is to permit the operator to apply to the tissue samples a volume of a preserving agent such as formalin while at the same time protecting the operator from exposure to said preserving agent.

- 20 Another advantage is to allow the operator to transfer the tissue samples from the temporary storage that is provided by the tissue-collecting device to a more permanent storage where fixation of samples is possible without having to physically manipulate individual samples.

- In the particular embodiment of the comprehensive tissue sampling system, these and other problems are solved by providing a tissue storage container that
25 comprises an essentially gas-tight enclosure when closed and has a lid that may be mated to the collecting unit lid with a snap-lock.

When the operator has detached the housing 5 – along with the collecting unit 4 and the collecting unit lid 6 – from the disposable unit, he may attach the storage container lid 7 to the collecting unit lid 6 by means of twin locking pins that are configured to mate with twin locking recesses in the collecting unit lid 6.

5 By twisting the tissue storage container lid in a counterclockwise direction, he may unscrew the collecting unit lid 6 from the housing 5. The collecting unit 4 along with the samples may then be removed from the housing 5, as shown in Fig. 14. Fig. 15 shows the collecting unit 4 mated to the tissue storage container lid 7.

10 Subsequent to removal of the housing 5, the rim of the tissue storage container lid 7 may be placed against the rim of the receptacle of the tissue storage container while the collecting unit 4 is inserted in the central hole of a plastic disc 10 that is removably placed over the trough of the receptacle and is a part of a user-activated seal between the tissue storage container lid and the
15 receptacle, as shown in Fig. 16. The arrow denominated "1" shows the direction of insertion of the collecting unit through the hole in the plastic disc 10. Immediately behind the plastic disc – and suspended centrally above the through of the receptacle – is placed a net that is configured to receive and enclose the collecting unit as well as the tissue samples that are held in their
20 individual tissue chambers.

To securely join the tissue storage container lid 7 and the receptacle 8, the operator may then twist the lid to a first locked position, as shown by the arrow denominated "2". In this position, properly configured seals of rubber or a
25 similar material ensure that the tissue storage container remains a gas-tight enclosure as soon as the tissue storage container lid has been twisted into said first locking position.

In addition, at least two locking pins in the collecting unit lid 7 are screwed into a threading in the rim of the net as the tissue storage container lid is twisted into its first locking position, ensuring that the net remains attached to the
30 collecting unit to keep the samples in place in the tissue chambers.

As the tissue storage container lid 7 is twisted to the first locked position, a plurality of holes in the plastic plate is aligned with a similar plurality of holes in a rubber membrane that comprises another part of a user-activated seal between the tissue storage container lid and the receptacle. Thus, a fluid
5 connection is established between the reservoir in the tissue storage container lid 7 and the receptacle 8. Fig. 17 shows the tissue storage container fully assembled and awaiting the ingress of the preserving agent.

The first locked position of the tissue storage container lid corresponds with the ingress stage. Accordingly, the operator may mate or connect a vessel 20
10 containing a preserving agent to the tissue storage container lid, as shown in Fig. 18. The arrow denominated "3" shows the direction of connection of the vessel 20.

In one particular embodiment, connection is accomplished by screwing a syringe containing formalin onto a female luer lock that is in operative connection with a
15 one-way valve, but other means of gas-tight connection between a vessel and an ingress means are also envisioned, such as a hypodermic needle that is inserted in a septum or a hose with a clamp that is pressed onto a spout.

Once a gas-tight connection has been accomplished, the operator may place the tissue storage container including the receptacle 8 and the lid 7 on a horizontal
20 surface with the bottom of the receptacle resting on said surface, and inject the contents of the vessel 20 (i.e. syringe) into the reservoir that is comprised in the tissue storage container lid. Injection is shown in Fig. 19, with the arrow denominated "4" showing the direction of motion of the syringe plunger.

The holes that are comprised in the rubber membrane and the plastic disc will
25 permit the preserving agent to run from the reservoir into the receptacle, while at the same time permitting air from the receptacle to flow into the tissue storage lid.

Following completion of the injection, the operator may remove the syringe from its gas-tight connection with the tissue storage container lid. In accordance with

the present embodiment, the one-way valve operatively connected to the female luer lock will prevent the escape of compressed air and vapors of preserving agent.

Subsequent to removal of the syringe, the operator may operate the user-
5 activated seal by twisting the tissue storage container lid to its second locked position, as shown in figure 20. The arrow denominated "5" shows the direction of twisting. During this, the plastic disc is held stationary by at least two ridges that are formed in the rim of the receptacle and are brought to rest against at least two locking bars that are formed in the plastic disc. The rubber
10 membrane, meanwhile, twists along with the tissue storage container lid, which causes the holes in the membrane to rotate out of alignment with the holes in the plastic disc. The combination of the inherent stiffness of the membrane material and the pressure exerted by the compressed air contained in the reservoir of the tissue storage container lid will ensure that the rubber
15 membrane is held against the plastic disc to provide a fluid-tight seal, effectively keeping the preserving agent contained in the receptacle during transport.

While the tissue storage container lid is twisted towards its second locked position, the at least two locking bars of the plastic disc slide into operative engagement with at least two locking recesses formed in the rim of the tissue
20 storage container lid 7. By suitable configuration of the locking bars and/or the locking recesses (e.g., by forming snap locks in either one or the other), the plastic disc may be mated to the tissue storage container lid. Since the plastic disc is removably placed over the through of the receptacle, it will stay attached to the tissue storage container lid when the lid is removed, pressing at all times
25 against the rubber membrane to maintain the fluid-tight seal

When the tissue storage container lid has been twisted to its second closed position, the tissue storage container along with the tissue samples may be sent to the pathologist for further analysis.

When the pathologist desires to further evaluate the tissue samples, he should
30 position the tissue storage container in a fume closet before removing the tissue

storage container lid from the receptacle. While the compressed air and vapors of preserving agent should be gas-tightly contained within the tissue storage container lid by the user-activated seal, a little compressed air will most likely be trapped between the surface of the preserving agent and the seal. Furthermore,
5 some preserving agent is bound to escape in gaseous form while the receptacle is open.

The pathologist should therefore leave the receptacle in the fume closet while removing the net from the collecting unit and samples from the collecting unit tissue chambers, whereupon he may reseal the receptacle by replacing the
10 tissue storage container lid.

It is understood that such a tissue storage system may also be adapted to function with other types of biopsy devices than the described multiple biopsy device. For instance, the individual tissue cores that are produced by conventional core needle devices may be placed on millipore paper, for
15 example, which in turn may be placed either in the main compartment of the receptacle or in the net of the receptacle. This will permit the operator to inject the preserving agent without exposure to the preserving agent.

Figs. 21-24 illustrate an embodiment of a tissue storage container, the lid of which itself constitutes a vessel for a preserving agent. As shown in Fig. 21, the
20 tissue storage container comprises a receptacle 80 for receiving the collecting unit 4 attached to a tissue storage container lid 70. The lid contains a volume of a tissue preserving agent, such as formalin. The receptacle is partially covered by a disc 81 having a central opening 84 for receiving the collecting unit 4. The disc also includes holes 82 for receiving a volume of preserving agent released
25 through apertures 72 provided in a lower portion of the lid 70, as described below. The apertures may optionally be closed or sealed. L-shaped projections 74 are provided on a rim portion of the tissue storage container lid 70. Upon axial displacement of the collecting unit 4 into the receptacle 4, the L-shaped projections 74 pass through interstices 85 formed in a rim portion 86 of the
30 receptacle 80. Depressions 76 in the L-shaped projections may subsequently

engage protrusions 87 in the rim portion 86 of the receptacle 80, as described further below.

In the state shown in Fig. 22, the tissue storage container lid 70 has been placed so that its lower rim portion abuts the rim portion 86 of the receptacle 80, with the collecting unit 4 placed in a trough of the receptacle 80. The lid 70 may then be twisted to the position shown in Fig. 23, i.e. to a first locked position, in which the holes 82 formed in the disc 81 of the receptacle 80 are aligned with the apertures 72 formed in the lower portion of the lid 70. As a consequence of twisting of the lid 70 to the position shown in Fig. 23, seals optionally closing the apertures 72 may be broken, e.g. ruptured by suitable rupturing structure provided e.g. on an upper surface of the disc 81. The volume of preserving agent in the lid 70 is then allowed to flow into the receptacle 80. Preferably, the volume of preserving agent in the lid 70 is just sufficient to fill the receptacle 80 to entirely cover the tissue sample(s) held by the collecting unit 4.

Finally, the lid 70 is twisted further as shown in Fig. 24 to a second locked position, in which the depressions 76 in the L-shaped projections 74 are engaged by the projections 87 of the rim portions 86 of the receptacle 80. In the second locked position, the apertures 72 are rotated beyond the holes 82 and hence fully covered by material of the disc 81, so that the preserving agent now contained in the vessel 80 is prevented from flowing back into the lid 70.

While this invention is susceptible of embodiment in many different forms, there is shown in the drawings and will herein be described in detail preferred embodiments of the invention with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the broad aspect of the invention to the embodiments illustrated.

CLAIMS

1. A tissue handling system comprising:
 - a biopsy device having an invasive unit with tissue-receiving and tissue-severing components being capable of harvesting and bringing at least one
 - 5 tissue sample to a point outside the body of a patient;
 - a tissue collecting device adapted to be brought in detachable operative engagement with the tissue-receiving components of the biopsy device to remove the at least one tissue sample;
 - a tissue storage container configured to receive the at least one tissue sample,
 - 10 the entire tissue collecting device, or the part of the collecting device that contains the at least one tissue sample, the tissue storage container further being configured to receive a volume of preserving agent; and
 - a vessel adapted to contain the preserving agent adapted to be gas-tightly mated or coupled to the tissue storage container.
- 15 2. A system according to claim 1, wherein the vessel has a compartment for storing the preserving agent, and wherein the compartment is closed by a liquid and gas tight closure, said closure being releasable when the vessel is mated or coupled to the tissue storage container.
- 20 3. A system according to claim 2, wherein the tissue storage container and the vessel comprise a connecting structure for gas-tightly mating or coupling the vessel to the tissue storage container, and wherein the connecting structure is arranged to cause said closure to be released as a consequence of mating or coupling the vessel to the tissue storage container.
- 25 4. A system according to any of the preceding claims, wherein the vessel is comprised in a lid for closing the tissue storage container.
5. A system according to claim 4, wherein the lid is attachable to the tissue storage container in such a way that a first attachment action establishes a gas tight coupling of the vessel to the tissue storage container, and a second attachment action causes release of said closure, the tissue storage container

and the lid being arranged such that the second attachment action cannot occur prior to the first attachment action.

6. A system according to claim 1, wherein the vessel includes a syringe, and wherein the tissue storage container comprises a connecting mechanism for gas-
5 tightly mating or coupling the syringe to the tissue storage container.

7. A system according to any of the preceding claims, wherein the collecting device comprises a collecting unit which comprises a plurality of individual tissue chambers, and wherein the collecting device is capable of sequentially removing, from the tissue-receiving components of the biopsy device, a plurality of
10 individual tissue samples as they are excised from the body of the patient and of temporarily storing the tissue samples in individual tissue chambers.

8. A system according to any of claims 1-6, wherein the collecting device comprises a collecting unit, which comprises a chamber, and wherein the collecting device is capable of sequentially removing, from the tissue-receiving
15 components of the biopsy device, a plurality of individual tissues samples as they are excised form the body of the patient and of temporarily storing the tissue samples in one single bulk in said chamber.

9. A system according to any of the preceding claims, wherein the vessel is adapted to contain a volume of preserving agent, which is sufficient to cover the
20 at least one tissue sample when stored in the tissue storage container.

10. A method of handling at least one harvested biopsy tissue sample, the method comprising:
- providing the at least one tissue sample in tissue-receiving components of a biopsy device outside the body of a patient;
25 - detachably engaging a tissue collecting device to said tissue-receiving components;
- arranging the at least one tissue sample, the entire tissue collecting device, or the part of the collecting device that contains the at least one tissue sample in a tissue storage container;

- gas-tightly mating or coupling a vessel containing a volume of a preserving agent to the tissue storage container;
- transferring the volume of preserving agent from the vessel to the tissue storage container, when the vessel is gas-tightly mated or coupled to the tissue storage container.

5

11. A method according to claim 10, wherein the vessel has a compartment for storing the preserving agent, and wherein the compartment is closed by a liquid and gas tight closure, and wherein said closure is released from a closed condition to an open condition, when the vessel is mated or coupled to the tissue storage container.

10

12. A method according to claim 11, wherein said closure is caused to be released as a consequence of mating or coupling the vessel to the tissue storage container.

13. A method according to claim 12, wherein the vessel is comprised in a lid for closing the tissue storage container, and wherein the lid is attached to the tissue storage container in such a way that a first attachment action establishes a gas tight coupling of the vessel to the tissue storage container, and a second subsequent attachment action causes release of said closure.

15

14. A method according to claim 13, comprising, subsequently to said step of transferring, the further step of conveying the tissue storage container with the at least one tissue sample container therein from a first handling site to a second handling site, when the tissue sample container is closed by said lid.

20

15. A system for storing at least one harvested biopsy tissue sample, the system comprising:

25

- a tissue storage container capable of receiving and storing the at least one tissue sample;
- a vessel containing a volume of a preserving agent;
- a connecting structure for gas-tightly mating or coupling the vessel to the tissue storage container;

- a fluid transferring mechanism for causing a transfer of the volume of preserving agent from the vessel to the tissue storage container, when the vessel is gas-tightly mated or coupled to the tissue storage container.

5 16. A system according to claim 15, wherein the vessel has a compartment for storing the preserving agent, and wherein the compartment is closed by a liquid and gas tight closure, said closure being releasable when the vessel is mated or coupled to the tissue storage container.

10 17. A system according to claim 16, wherein the tissue storage container and the vessel comprise a connecting structure for gas-tightly mating or coupling the vessel to the tissue storage container, and wherein the connecting structure is arranged to cause said closure to be released as a consequence of mating or coupling the vessel to the tissue storage container.

18. A system according to any of claims 15-17, wherein the vessel is comprised in a lid for closing the tissue storage container.

15 19. A system according to claim 18, wherein the lid is attachable to the tissue storage container in such a way that a first attachment action establishes a gas tight coupling of the vessel to the tissue storage container, and a second attachment action causes release of said closure, the tissue storage container and the lid being arranged such that the second attachment action cannot occur
20 prior to the first attachment action.

20. A system according to claim 15, wherein the vessel includes a syringe, and wherein the tissue storage container comprises a connecting mechanism for gas-tightly mating or coupling the syringe to the tissue storage container.

25 21. A system according to any of claims 15-20, wherein the vessel is adapted to contain a volume of preserving agent, which is sufficient to cover the at least one tissue sample when stored in the tissue storage container.

22. A vessel for a system according to any of claims 15-21, said system comprising a tissue storage container capable of receiving and storing at least one tissue sample, the vessel comprising:

- a cavity containing a volume of a tissue preserving agent;

5 - connecting elements for gas-tightly mating or coupling the vessel to the tissue storage container;

- fluid transferring element for causing a transfer of the volume of preserving agent from the vessel to the tissue storage container, when the vessel is gas-tightly mated or coupled to the tissue storage container.

10 23. A vessel according to claim 22, comprising a compartment for storing the preserving agent, and wherein the compartment is closed by a liquid and gas tight closure, said closure being releasable when the vessel is mated or coupled to the tissue storage container.

15 24. A vessel according to claim 22, the vessel being comprised in a lid for closing the tissue storage container.

1/16

Fig. 1





Fig. 2



2/16




Fig. 3

3/16




Fig. 4

4/16




Fig. 5

5/16

Fig. 6






Fig. 7



6/16

Fig. 8



7/16

Fig. 9





Fig. 10



8/16

Fig. 11





Fig. 12



9/16

Fig. 13





Fig. 14



10/16

Fig. 15





Fig. 16



11/16




Fig. 17

12/16




Fig. 18

13/16




Fig. 19

14/16

Fig. 20





Fig. 21



15/16

Fig. 22






Fig. 23



16/16

Fig. 24



INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2007/060615

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61B10/00 A61B10/02 B01L3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B B01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98/46290 A (VACSAX LIMITED [GB]; BENNETT JOHN [GB]) 22 October 1998 (1998-10-22)	15-17, 20-23
Y	page 3, line 16 - page 8, line 14; figures 1,2,5,6A-D	1-3,6-12
A		5,13,14, 19
X	WO 99/33501 A (T C T PRODUCTS LTD [IL]; SHARON IGAL [IL]; INBAR MICHAEL [IL]) 8 July 1999 (1999-07-08)	15,16, 18,21-24
Y	page 8, line 1 - page 10, line 17; figure 1	4
	----- -/--	

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

20 February 2008

Date of mailing of the international search report

28/02/2008

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Øen, Petter

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2007/060615

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 526 822 A (BURBANK FRED H [US] ET AL) 18 June 1996 (1996-06-18) cited in the application column 13, line 1 - column 15, line 36; figures 4-6 -----	1-4,6,7, 9-12
Y	US 2005/027210 A1 (MILLER MICHAEL E [US]) 3 February 2005 (2005-02-03) paragraph [0027]; figure 2 -----	8
A	EP 1 656 889 A (OLYMPUS CORP [JP]; OLYMPUS MEDICAL SYSTEMS CORP [JP]) 17 May 2006 (2006-05-17). abstract; figures 2A-B -----	1-14
A	US 5 554 151 A (HINCHLIFFE PETER W J [US]) 10 September 1996 (1996-09-10) column 4, lines 18-22 -----	15-24
A	WO 2006/038634 A (OLYMPUS CORP [JP]; ITOH TOMOKO [JP]; FUKUOKA MORINAO [JP]; KAWAI TSUYO) 13 April 2006 (2006-04-13) abstract; figures 6-10 & EP 1 806 090 A (OLYMPUS CORP [JP]) 11 July 2007 (2007-07-11) paragraph [0064] - paragraph [0091]; figures 6-10 -----	1-14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2007/060615

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9846290	A	22-10-1998	AU 6929298 A GB 2323288 A	11-11-1998 23-09-1998
WO 9933501	A	08-07-1999	AU 1575699 A	19-07-1999
US 5526822	A	18-06-1996	CA 2186283 A1 DE 69535416 T2 EP 0751744 A1 JP 3650117 B2 JP 9510638 T JP 3769288 B2 JP 2005199044 A WO 9525465 A2 US 5775333 A	28-09-1995 20-12-2007 08-01-1997 18-05-2005 28-10-1997 19-04-2006 28-07-2005 28-09-1995 07-07-1998
US 2005027210	A1	03-02-2005	EP 1651115 A1 JP 2007500557 T WO 2005011505 A1	03-05-2006 18-01-2007 10-02-2005
EP 1656889	A	17-05-2006	JP 2006141441 A US 2006116603 A1	08-06-2006 01-06-2006
US 5554151	A	10-09-1996	NONE	
WO 2006038634	A	13-04-2006	CN 101035459 A EP 1806090 A1 KR 20070050496 A US 2007213632 A1	12-09-2007 11-07-2007 15-05-2007 13-09-2007
EP 1806090	A	11-07-2007	CN 101035459 A WO 2006038634 A1 KR 20070050496 A US 2007213632 A1	12-09-2007 13-04-2006 15-05-2007 13-09-2007